




**NON-POTABLE WATER  
DO NOT DRINK**  
To conserve water,  
this building uses reclaimed  
water to flush toilets and urinals.

**SLOAN.**



# Royal® Model Reclaimed Water Flushometer

# 186 HEU RW

### Description

Exposed high-efficiency urinal Flushometer, for 3/4" top spud high-efficiency urinals. For installations where reclaimed or recycled water is used for flushing.

### Flush Cycle

- Model 186-0.125 RW High-Efficiency (0.125 gpf/0.5 Lpf)
- Model 186-0.25 RW High-Efficiency (0.25 gpf/1.0 Lpf)
- Model 186-0.5 RW High-Efficiency (0.5 gpf/1.9 Lpf)

### Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- 3/4" I.P.S. Screwdriver Bak-Chek® Angle Stop w/ Free Spinning Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum breaker flush connection w/ one-piece bottom hex coupling nut
- Spud Coupling and Flange for 3/4" Top Spud
- Red Brass Sweat Solder Adapter w/Cover Tube & Cast Wall Flange w/Set Screw
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID Technology
- Handle Packing, Stop Seat and Vacuum Breaker molded from PERMEX Synthetic Rubber Compound for Chloramine Resistance
- Includes adhesive backed metal wallplate with non-potable water warning
- Features purple wall flange, diaphragm guide, bonnet and inner cover to communicate reclaimed water use

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037 and ANSI/ASME A112.19.2.

### Variations

- XYV** Valve Less Vacuum Breaker
- SG** SaniGuard® Antimicrobial Coating Protects Handle and Socket\*
- PH** Purple Handle

### Special Finishes

- PVDPB** Polished Brass
- PVDBN** Brushed Nickel
- PVDSF** Satin Chrome

\* SaniGuard does not protect users or others against disease-causing bacteria.

### Accessories

See Accessories Section of the Sloan catalog for details on these and other flushometer variations.

### Fixtures

Contact Sloan for Sloan brand matching fixture options.

This space for Architect/Engineer approval	
Job Name _____	Date _____
Model Specified _____	Quantity _____
Variations Specified _____	
Customer/Wholesaler _____	
Contractor _____	
Architect _____	

The information contained in this document is subject to change without notice.



**SLOAN • 10500 SEYMOUR AVENUE • FRANKLIN PARK, IL 60131**  
Ph: 1-800-982-5839 • Fax: 1-800-447-8329 • www.sloanvalve.com

Made In The  
**USA**

